



TECHNICAL DATA SHEET

ECOSAR 116/1000

● SUMMARY ADHESIVE IN WATER DISPERSION, WITH A BASIS OF SYNTHETIC LATEX

● **USE** It is particularly suitable for leather goods, for coupling of leather and synthetic material.
It can be applied by brush, by gun-spray and roll-machine.

● **CHARACTERISTICS**

- Appearance	liquid of ivory white colour
- Viscosity: (Brook, RVT, 20°C)	800-1400 cps (G3 – V20)
- pH value	between 8 and 9
- Solid content	49,5 +/- 2,5

● **APPLICATION**

- **ECOSAR 116/1000** has to be applied on both surfaces to be bond
- let dry minimum 10 minutes then press the two surfaces
- during the spraying operation it is necessary to adjust the distance of spraying gun in order to obtain an homogeneous spraying
- open time till 1 hour

Notes: it is suggested to use the adhesive at temperatures not lower than 18°; in case the material is stocked in cold ambients, recondition before using

● **PACKING** Bucket of Kg. 10 - carton of n. 2 buckets

● **STORAGE** Shelf life: 6 months if kept in its original packings at a temperature of 20°C.
Keep the product from freezing and at a temperature not lower than + 10°C.

● **NOTE** Stir it well before its use.
Keep from freezing.
Keep the packings perfectly closed.

This information is to the best of our knowledge true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

29-08-2014 RM/pm