QUALITY MANAGEMENT
SYSTEM
CERTIFIED ISO 9001

TECHNICAL DATA SHEET

ECOSAR MW 116 AD

- *SUMMARY* — **ADHESIVE IN WATER DISPERSION, WITH A BASIS OF SYNTHETIC LATEX**

- *USE* — It is particularly suitable for leathers goods, for coupling of leather and synthetic material. It can be applied by brush.

- *CHARACTERISTICS*

– Appearance	ivory white liquid
– Viscosity: (Brook, RVT, 20°C) (needle 2, rotations 5)	5400 +/- 500 (mPas)
– pH value	between 8 and 9
– Solids content	49,5 +/- 2,5

- *APPLICATION*
  - **ECOSAR MW 116 AD** has to be applied on both surfaces to be bond
  - during the brushing operation take care of homogeneous application
  - let dry minimum 10 minutes and then press
  - open time till 1 hour

  Notes: it is suggested to use the adhesive at temperatures not lower than 18°; in case the material is stocked in cold ambients, recondition before using

- *PACKING* — 10 Kg. cans - box of no. 2 cans

- *STORAGE* — Stable for 6 months if kept carefully in original packaging at a temperature of 20°C. The product must be kept away from cold and stored at an ambient temperature not below + 10°C.

- *NOTE* — Stir well before use. Avoid frost. Keep the packaging tightly sealed.

This information is to the best of our knowledge true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

15-02-10 SG/pm

KENDA FARBEN S.p.A. Via Tramia, 72 - 27026 GARLASCO PV - ITALY - P.O. Box 42 - Tel. +39 0382 820201 - Fax +39 0382 820205
http://www.kendafarben.com - E-mail: info@kendafarben.com