QUALITY MANAGEMENT SYSTEM
CERTIFIED ISO 9001

TECHNICAL DATA SHEET **Series** **311704**

PRIMER EVA

- *SUMMARY* **COLOURLESS, PRIMER FOR EVA**

- *CHARACTERISTICS*
  - Colour colourless - light yellow
  - Specific gravity at 20°C 0,800 +/- 0,01
  - Of easy flammability

- *APPLICATION*
  - By means of a small brush apply **PRIMER EVA** onto the EVA, if previously sanded increased performance bonding
  - let dry for 15 - 20 minutes at room temperature
  - then apply the final polyurethane adhesive added with 3 - 5% of hardener
  - once the solvents have evaporated reactivate the adhesive film and couple exercizing a uniform pressure
  - final adhesion after 48 hours

- *COLOURS*

- *SOLVENTS*

- *PACKING* Tin of Kg. 8 - carton of n. 2 tins

- *STORAGE* Shelf life: about 24 months if stored in well closed original packings in a dry and airy place.
  Keep from freezing and extreme heat.

This information is to the best of our knowledge true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

03-09-2015 RM/pm

KENDA FARBEN S.p.A. Via Tramia, 72 - 27026 GARLASCO PV - ITALY - P.O. Box 42 - Tel. +39 0382 820201 - Fax +39 0382 820205
http://www.kendafarben.com - E-mail: info@kendafarben.com